

REMARKS

The rejection of Claims 1-7 under 35 U.S.C. § 102(b) as anticipated by WO 95/12623 (Hentges et al), is respectfully traversed.

Hentges et al is drawn to hydrogenated hydrocarbon resins, methods of preparation and uses as tackifiers for adhesive compositions comprising polar-group containing copolymers, particularly acrylic copolymers (page 1, lines 5-7), which hydrogenated hydrocarbon resins have a ring and ball softening point of from 40°C to about 120°C (page 2, lines 34-35). While Hentges et al does not disclose a particular softening point range for their resin prior to hydrogenation, it is noted that all of the examples therein, i.e., Resin Examples A through E, have softening points from 88°C to 112°C prior to hydrogenating. See Table II (page 11). Nor does Hentges et al disclose or suggest the presently-recited hydrogenated copolymer, i.e., a hydrogenated copolymer of cyclopentadiene and/or dicyclopentadiene with a vinyl-substituted aromatic compound. While Hentges et al discloses dicyclopentadiene *per se*, it is as a typical chain transfer agent, not as a monomer in the preparation of a copolymer. See Table IB at page 10.

For all the above reasons, it is respectfully requested that this rejection be withdrawn.


The rejection of Claims 1 and 3 under 35 U.S.C. § 112, second paragraph as indefinite, is respectfully traversed. There are **no** conflicting limitation ranges for softening points. It is clear that the 45 to 55°C range is for the copolymer prior to its being hydrogenated; and the range of 85 to 95°C is for the hydrogenated copolymer. Accordingly, it is respectfully requested that this rejection be withdrawn.

All of the presently-pending claims in this application are now believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to pass this application to issue.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,  
MAIER & NEUSTADT, P.C.

Norman F. Oblon



Harris A. Pitlick  
Registration No. 38,779

Customer Number  
**22850**

Tel: (703) 413-3000  
Fax: (703) 413 -2220  
(OSMMN 03/06)

NFO:HAP\la